

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

Claim 1 (previously presented): A method of activating an inactive terminal (6) of a data network (1), which terminal is connected to a telephone network (4), for establishing a connection through the data network (1) between a further terminal (5) and the terminal (6) to be activated,

characterized by the following steps:

- establishing a connection to a server (11) of the data network (1) and transmitting an identifier of the terminal (6) to be activated to the server (11) of the data network (1);
- receiving the identifier at the server (11) of the data network (1);
- interpreting the identifier at the server (11) of the data network (1) to determine the telephone number of the terminal (11) to be activated;
- making a telephone call from the server (11) of the data network (1) through the telephone network (4) to the terminal (6) to be activated;
- signaling the identity of the server (11) of the data network through the telephone network (4) to the terminal (6) to be activated;
- receiving the telephone call and interpreting the signaling at the terminal (6) to be activated;

- terminating the telephone call to the terminal (6) by the server (11) of the data network (1);
and
- establishing a connection from the terminal (6) to be activated to the data network (1) if the signaling indicates that the telephone call came from a server (11) of the data network (1).

Claim 2 (original): A method as claimed in claim 1, characterized in that the establishment of the connection to the server (11) of the data network (1) and the transmission of the identifier of the terminal (6) to be activated to the server (11) of the data network (1) are effected by the further terminal (5).

Claim 3 (previously presented): A method as claimed in claim 1, characterized in that, in order to establish a connection between the further terminal and the terminal to be activated,

- the terminal (6) to be activated establishes a connection to a server (11) of the data network (1) and transmits its identifier to the server (11) or the identifier is determined by the server (11);
- the data network addresses of the two terminals (5, 6) are transmitted by the server (11) of the data network to the respective other terminal (5; 6), or are retrieved by the terminals (5, 6) from the server (11); and
- a connection is established by the terminals (5, 6) through the telephone network (4) and the data network (1).

Claim 4 (previously presented): A method as claimed in claim 1, characterized in that the data network (1) is designed as an Internet Protocol (IP) network.

Claim 5 (previously presented): A method as claimed in claim 4, characterized in that the further terminal (5) is a calling party's terminal (5) connected to a telephone network (4), and in that the terminal (6) to be activated is a called party's terminal (6) connected to the telephone network (4), the called party's terminal (6) being activated to set up a voice call between the calling party's terminal (5) and the called party's terminal (6) through the IP network (1).

Claim 6 (previously presented): A method as claimed in claim 5, characterized by the following steps:

- The calling party dials at his or her terminal (5) the telephone number of the terminal (6) of the called party;
- a first Voice-over-IP (VoIP) adapter unit (9), connected between the terminal (5) of the calling party and the telephone network (4), receives the dialed telephone number;
- the first VoIP adapter unit (9) establishes a connection through the telephone network (4) to a POP server (2) and through the latter to the data network (1);
- the first VoIP adapter unit (9) transmits the called-party telephone number and its own IP address over the IP network (1) to a VoIP server (11) of the data network (1);

- the VoIP server (11) receives the called-party telephone number and the IP address of the first VoIP adapter unit (9);
- the VoIP server (11) dials up the terminal (6) of the called party through the telephone network (4);
- over the telephone network (4), the telephone number of the VoIP server (11) is signaled to the terminal (6) of the called party;
- a second VoIP adapter unit (10), connected between the terminal (6) of the called party and the telephone network (4), receives the telephone number of the VoIP server (11);
- the second VoIP adapter unit (10) compares the telephone number with telephone numbers of known VoIP servers;
- the second VoIP adapter unit (10) identifies the VoIP server (11) and prevents the incoming call from being transferred to the terminal (6) of the called party;
- the second VoIP adapter unit (10) establishes a connection to a POP server (3) through the telephone network (4);
- the second VoIP adapter unit (10) transmits its IP address to the VoIP server (11) over the IP network (1);
- the VoIP server (11) transmits the IP address of the first VoIP adapter unit (9) to the second VoIP adapter unit (10), and the VoIP server (11) transmits the IP address of the second VoIP adapter unit (10) to the first VoIP adapter unit (9);

- an IP connection is established from the first VoIP adapter unit (9) to the second VoIP adapter unit (10);
- the second VoIP adapter unit (10) causes a telephone call to be sent to the terminal (6) of the called party; and
- a voice call is established between the terminal (5) of the calling party and the terminal (6) of the called party if the called party accepts the telephone call.

Claim 7 (original): A method as claimed in claim 6, characterized in that the VoIP server (11) and the POP server (2; 3) are combined in a common POP/VoIP server.

Claim 8 (previously presented): A server (11) of a data network, characterized by

- means for receiving from a terminal (5) an identifier of a terminal (6) to be activated, which is connected to a telephone network (4);
- means for making a telephone call over the telephone network (4) to the terminal (6) to be activated; and
- means for terminating the telephone call to the terminal (6) to be activated.

Claim 9 (original): A server (11) as claimed in claim 8, characterized in that it is designed as an access server (2; 3) of an IP network (1).

Claim 10 (previously presented): A server (11) as claimed in claim 8, further comprising means for interpreting the identifier and determining the telephone number of the terminal (6) to be activated.

Claim 11 (previously presented): A server (11) as claimed in claim 8, characterized in that the server (2, 3, 11) further comprises means for accepting a telephone call received from the terminal (5) over the telephone network (4), and means for establishing a connection from the terminal (5) to the data network (1).

Claim 12 (previously presented): An adapter unit (9) connected between a terminal (5; 6) of a telephone network (4) and the telephone network (4), characterized by

- means for establishing a connection from the terminal (5) to a server (2; 3) of a data network (1) over the telephone network (4);
- means for receiving a telephone call of a server (11) of the data network (1);
- means for interpreting a telephone number of a caller;
- means for comparing the telephone number of the caller with the telephone numbers of known servers of the data network;

- means for retrieving and/or receiving a data network address of a further adapter unit (10; 9) from the server of the data network (1); and
- means for establishing a data call to the further adapter unit (10; 9) through the data network (1).

Claim 13 (previously presented): An adapter unit (9; 10) as claimed in claim 12, further comprising means for transmitting the identifier of a terminal (6) to be activated or the identification of a called party to the server (2; 3) of the data network (1).

Claim 14 (previously presented): An adapter unit (9; 10) as claimed in claim 12, characterized by being implemented as a microcomputer with a processor, a memory, an interface to the telephone network (4), and an interface to an Internet Protocol (IP) network (1).

Claim 15 (previously presented): A telephone (5, 6) configured for connection to a telephone network (4), characterized in that an adapter unit (9; 10) is incorporated in the telephone (5, 6), said adapter unit comprising:

- means for establishing a connection from the telephone (5, 6) to a server (2; 3) of a data network (1) over the telephone network (4);
- means for receiving a telephone call of a server (11) of the data network (1);

- means for interpreting a telephone number of a caller;
- means for comparing the telephone number of the caller with telephone numbers of known servers of the data network;
- means for retrieving and/or receiving a data network address of a further adapter unit (10; 9) from the server of the data network (1); and
- means for establishing a data call to the further adapter unit (10; 9) through the data network (1).

Claim 16 (previously presented): A microcomputer comprising a modulator-demodulator (modem) or an ISDN adapter, wherein the modem or the ISDN adapter being configured for connection to a telephone network (4), and including an adapter unit (9, 10), said adapter unit (9, 10) comprising:

- means for establishing a connection from the microcomputer to a server (2; 3) of a data network (1) over the telephone network (4);
- means for receiving a telephone call of a server (11) of the data network (1);
- means for interpreting a telephone number of a caller;
- means for comparing the telephone number of the caller with telephone numbers of known servers of the data network;

- means for retrieving and/or receiving a data network address of a further adapter unit (10; 9) from the server of the data network (1); and
- means for establishing a data call to the further adapter unit (10; 9) through the data network (1).

Claim 17 (previously presented) A microcomputer as claimed in claim 16, wherein said microcomputer is a personal computer.

Claim 18 (currently amended) ~~A method as claimed in claim 1,~~ A method of activating an inactive terminal (6) of a data network (1), which terminal is connected to a telephone network (4), for establishing a connection through the data network (1) between a further terminal (5) and the terminal (6) to be activated,
characterized by the following steps:

- establishing a connection to a server (11) of the data network (1) and transmitting an identifier of the terminal (6) to be activated to the server (11) of the data network (1);
- receiving the identifier at the server (11) of the data network (1);
- interpreting the identifier at the server (11) of the data network (1) to determine the telephone number of the terminal (11) to be activated;

- making a telephone call from the server (11) of the data network (1) through the telephone network (4) to the terminal (6) to be activated;
 - signaling the identity of the server (11) of the data network through the telephone network (4) to the terminal (6) to be activated; and
 - receiving the telephone call and interpreting the signaling at the terminal (6) to be activated;
- wherein, when said terminal (6) to be activated receives the telephone call and interprets the signaling, said terminal (6) to be activated does not accept the telephone call from the server (11) if said terminal (6) to be activated recognizes the signaling as being from the server (11).

Claim 19 (currently amended): ~~An adapter unit (9; 10) as claimed in claim 12,~~ An adapter unit (9) connected between a terminal (5; 6) of a telephone network (4) and the telephone network (4), characterized by

- means for establishing a connection from the terminal (5) to a server (2; 3) of a data network (1) over the telephone network (4);
- means for receiving a telephone call of a server (11) of the data network (1);
- means for interpreting a telephone number of a caller; and
- means for comparing the telephone number of the caller with the telephone numbers of known servers of the data network;

Amendment under 37 C.F.R. § 1.116
U.S. Application No. 09/676,675

wherein the adapter unit (9) does not accept the telephone call from the server (11) of the data network (1) if said means for comparing determines that the telephone number of the caller is a telephone number of a known server of the data network.